

HIGH PERFORMANCE ENGINEERED PLASTIC PUMPS

PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	REQUIRED CONTROLLERS	10	20	40	50	70	80	85	100	110	120	140	150	180	200
MEGA-TYPHOON with 90' of wire	P-10350	POWER BOOSTER 1 (PA-10600) OR LOW FLOW WITH POWER BOOSTER 1 (PA-10650)	3.5 G.P.M 12V.	3.1 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	.5 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
SUPER TWISTER with 90' of wire	P-10275	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	2.5 G.P.M 12V.	2.0 G.P.M 12V.	1.50 G.P.M 12V.	1.25 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.50 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TSUNAMI with 110' of wire	P-10400	POWER BOOSTER 2 (PA-10700) OR LOW FLOW WITH POWER BOOSTER 2 (PA-10750)	4.0 G.P.M 12V.	3.8 G.P.M 12V.	3.2 G.P.M 12V.	3.0 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.50 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A
MONSOON with 130' of wire	P-10500	POWER BOOSTER 2 (PA-10700) OR LOW FLOW WITH POWER BOOSTER 2 (PA-10750)	4.4 G.P.M 12V.	4.2 G.P.M 12V.	3.5 G.P.M 12V.	2.8 G.P.M 12V.	2.1 G.P.M 12V.	1.9 G.P.M 12V.	1.6 G.P.M 12V.	1.5 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	N/A	N/A	N/A	N/A
HURRICANE with 160' of wire	P-10510	POWER BOOSTER 2 (PA-10700) OR LOW FLOW WITH POWER BOOSTER 2 (PA-10750)	4.5 G.P.M 12V.	4.0 G.P.M 12V.	3.0 G.P.M 12V.	2.75 G.P.M 12V.	2.25 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.35 G.P.M 12V.	1.25 G.P.M 12V.	1.15 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A
MEGA-MONSOON with 210' of wire	P-10520	LOW FLOW WITH POWER BOOSTER 3 (PA-10850)	4.0 G.P.M 12V.	3.75 G.P.M 12V.	2.75 G.P.M 12V.	2.5 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.75 G.P.M 12V.	1.65 G.P.M 12V.	1.65 G.P.M 12V.	1.5 G.P.M 12V.	.65 G.P.M 12V.	.50 G.P.M 12V.	.30 G.P.M 12V.	.15 G.P.M 12V.