

STAINLESS STEEL (SS) PUMPS

PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	REQUIRED CONTROLLER	10	20	30	40	60	70	80	100	110	120	130	150
SS-MINI MONSOON with 90' of wire	PS-10405	NOT COMPATIBLE WITH ANY OF PROACTIVE'S CONTROLLERS	1.75 G.P.M 12V.	1.25 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A
SS-MEGA-TYPHOON with 90' of wire	PS-10350	LOW FLOW WITH POWER BOOSTER 1 "LCD" CONTROLLER (PA-10660)	3.0 G.P.M 12V.	2.75 G.P.M 12V.	2.55 G.P.M 12V.	2.0 G.P.M 12V.	1.0 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A
SS-MONSOON with 130' of wire	PS-10400	LOW FLOW WITH POWER BOOSTER 2 "LCD" CONTROLLER (PA-10670)	3.5 G.P.M 12V.	3.25 G.P.M 12V.	3.0 G.P.M 12V.	3.0 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	.50 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A
SS-HURRICANE with 160' of wire	PS-10415	LOW FLOW WITH POWER BOOSTER 2.5 "LCD" CONTROLLER (PA-10675)	3.5 G.P.M 12V.	3.25 G.P.M 12V.	3.0 G.P.M 12V.	3.0 G.P.M 12V.	2.5 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.25 G.P.M 12V.	1.25 G.P.M 12V.	1.0 G.P.M 12V.	.85 G.P.M 12V.	.50 G.P.M 12V.