

STANDARD ENGINEERED PLASTIC PUMPS

PUMPING DEPTH IN FEET

PUMP MODEL	ITEM NO.	OPTIONAL CONTROLLER	3	10	20	25	30	40	50	55	60	70	85	90
CYCLONE with 35' of wire	P-10100	LOW FLOW SAMPLING CONTROLLER (PA-10800)	2.0 G.P.M 12V.	1.0 G.P.M 12V.	.35 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
MINI-TYPHOON with 50' of wire	P-10150	LOW FLOW SAMPLING CONTROLLER (PA-10800)	2.5 G.P.M 12V.	2.2 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A	N/A
TYPHOON with 60' of wire	P-10200	LOW FLOW SAMPLING CONTROLLER (PA-10800)	3.0 G.P.M 12V.	2.3 G.P.M 12V.	2.0 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.6 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A	N/A	N/A	N/A
TEMPEST / TWISTER with 70' of wire	P-10250	LOW FLOW SAMPLING CONTROLLER (PA-10800)	3.2 G.P.M 12V.	2.8 G.P.M 12V.	2.2 G.P.M 12V.	2.0 G.P.M 12V.	1.75 G.P.M 12V.	1.2 G.P.M 12V.	.75 G.P.M 12V.	.60 G.P.M 12V.	.40 G.P.M 12V.	N/A	N/A	N/A
MINI-MONSOON with 80' of wire	P-10300	LOW FLOW SAMPLING CONTROLLER (PA-10800)	4.0 G.P.M 12V.	3.2 G.P.M 12V.	2.8 G.P.M 12V.	2.5 G.P.M 12V.	2.2 G.P.M 12V.	1.5 G.P.M 12V.	1.0 G.P.M 12V.	.75 G.P.M 12V.	.60 G.P.M 12V.	.25 G.P.M 12V.	N/A	N/A
TORNADO with 90' of wire	P-10330	LOW FLOW SAMPLING CONTROLLER (PA-10800)	4.25 G.P.M 12V.	3.75 G.P.M 12V.	3.5 G.P.M 12V.	3.25 G.P.M 12V.	3.0 G.P.M 12V.	2.5 G.P.M 12V.	1.75 G.P.M 12V.	1.25 G.P.M 12V.	.75 G.P.M 12V.	.50 G.P.M 12V.	.35 G.P.M 12V.	N/A

PUMP MODEL	ITEM NO.	OPTIONAL CONTROLLER	10	20	40	60	80	100	120	140	160	180	200	220
ABYSS with 230' of wire	P-10380	LOW FLOW SAMPLING CONTROLLER (PA-10800)	1.15 G.P.M 12V.	1.0 G.P.M 12V.	1.0 G.P.M 12V.	.85 G.P.M 12V.	.85 G.P.M 12V.	.80 G.P.M 12V.	.80 G.P.M 12V.	.75 G.P.M 12V.	.75 G.P.M 12V.	.70 G.P.M 12V.	.70 G.P.M 12V.	.50 G.P.M 12V.